

MAGO

SPECIAL PRODUCT FOR DESCALING AND DEGREASING OF HARD SURFACES AND POOL WALLS

PROPERTIES:

THE BALANCED AND SPECIALLY CONCEIVED FORMULA OF **MAGO** ENABLES IT TO REMOVE RAPIDLY EVEN THE TOUGHEST RESIDUES OF KIND OF CALCAREOUS SCALING FORMATIONS AND FAT WASTE.

THE PRESENCE OF CORROSION INHIBITORS PRESERVES ANY KIND OF SURFACE CORROSION.

USE AND DOSAGE:

DEPENDING ON THE CASE, THE PRODUCT CAN BE APPLIED PURE OR DILUTED AND ALLOW IT TO WORK FOR A MAXIMUM TIME OF 5 MINUTES

FOR ORDINARY MAINTENANCE USE THE PRODUCT DILUTET AT 5 - 10 %.

DO PRELIMINARY TESTS OF COMPATIBILITY WITH MATERIALS SURFACES. IT IS RECOMMENDED NOT TO USE THIS PRODUCT ON GALVANIZED, COPPER, CHROMED, PAINTED SURFACES, ON MARBLE, CEMENT AND DECORATED POTTERY.

ALLOWING IT TO ACT FOR THE SPECIFIED AMOUNT OF TIME AND THEN RINSING OFF WITH COPIOUS AMOUNTS OF WATER.

MAIN USES:

REMOVAL OF CALCAREOUS AND FAT RESIDUES FROM POOL WALLS, CERAMIC AND FLORENCE TERRA COTTA FLOORS.

PARTICULAR COMPATIBILITY WARNINGS WITH MATERIALS

DO PRELIMINARY TESTS OF COMPATIBILITY WITH MATERIALS BEFORE USE THE PRODUCTS, TESTING IT ON A SMALL PART OF SURFACE.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	RED LIQUID
ODOR	PUNGENT
SOLUBILITY IN WATER	COMPLETE
pH of PRODUCT "AS IS"	< 1
pH (1% solution)	1 - 2
SPECIFIC GRAVITY AT 25°C	1,10 +/-0.02 Kg/l

CHECKS:

LEGAL REFERENCES

WARNINGS AND HAZARDS IDENTIFICATION

PRODUCT IS **CORROSIVE**:

HAZARD STATEMENTS:

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

H318 CAUSES SERIOUS EYE DAMAGE.

H335 MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENTS:

P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P280 WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P301+P330+P331 IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING.

P303+P361+P353 IF ON SKIN (OR HAIR): REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER.

P305+P351+P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

P310 IMMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN.

P501 DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH APPLICABLE REGULATIONS.

EXPOSURE CONTROLS/ PERSONAL PROTECTION

RESPIRATORY PROTECTION: FACE MASK COMPLETE WITH ACID FILTER

HAND PROTECTION: GLOVES.

EYE PROTECTION: TOTAL SAFETY GOGGLES

CLOTHING: PROTECTIVE CLOTHING

TLV LIMITS: TLV LIMITS NOT ESTABLISHED

HANDLING AND STORAGE

HANDLE WEARING RUBBER GLOVES AND SAFETY GOGGLES. STORE AT ROOM-TEMPERATURE AND PROTECTED AGAINST DIRECT SUNLIGHT.

AVOID CONTACT WITH ORGANIC MATTER.

FIRST-AID MEASURES

SKIN: REMOVE ANY CONTAMINATED CLOTHING IMMEDIATELY. WASH THE AFFECTED AREAS WITH COPIOUS AMOUNTS OF FLOWING WATER.

EYE: WASH EYES WITH COPIOUS AMOUNTS OF FLOWING WATER IMMEDIATELY, GENTLY PRIZING OPEN EYELIDS TO ENSURE EFFICIENT WASHING. IF NECESSARY, ASK FOR A SPECIALISTIC EXAMINATION.

INGESTION: WASH OUT MOUTH WITH COPIOUS AMOUNTS OF WATER AND DRINK WATER OR MILK OR EGG WHITE. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

INHALATION: REMOVE THE PERSON TO AN UNCONTAMINATED AREA; IF THE PERSON'S BREATHE IS IRREGULAR OR INTERRUPTED, PRACTICE ARTIFICIAL RESPIRATION. SEEK MEDICAL HELP AS SOON AS POSSIBLE.

COMPOSITION:

IT CONTAIN CHLORIDIC CONC. ACID < 25 % ,PHOSPHORIC CONC. ACID < 10 % CO-FORMULANTS AND ALIPHATIC CORROSION INHIBITORS

PACKAGING

10 LT. BARREL

TRANSPORT INFORMATION

TRANSPORT BY ROAD: UN 1760, CORROSIVE LIQUID N.A.S. 8, III ADR.