

Solution for Water Treatment

Pool Line

TECHNICAL SHEET N° 422

MULTIACTION 200 gr. TABLET

CHLORINATOR AGENT STABILIZED WITH FLOCCULANT AND ANTIALGAE

IDENTIFICATION OF THE SUBSTANCE':

SLOW DISSLOLUTION CHLORINATED AGENT, WITH FLOCCULANT AND ATIALGAE. PRODUCT IS APPROPRIATE FOR MANUAL DOSING ON THE "SKIMMER" OR USING SPECIFIC "UNDER PRESSURE DOSING SYSTEM".

USE AND DOSAGE :

PUT 1 OR 2 TABLETS IN THE BASKET OF ANY SKIMMER. IF THERE ARE CONTINUE "BY-PASS" SYSTEMS OF CHLORINATION, FILL UNTIL 2/3 THE CONTAINER DOOR PADS. THE DOSES ARE VALUED CASE TO CASE FOR ENSURE CONSTANT IN TANK THE CONCENTRATION OF CHLORINE FROM 0.7 to 1.5 ppm, IN AGREEMENT WITH LAW OF THE COUNTRY.

INDICATIVE DOSE: 2-3 GRAMS PER CUBIC METRE OF WATER PER DAY.

CONSUMPTION CAN 'CHANGE IN A FUNCTION OF TEMPERATURE, INTENSITY' LIGHT OF FREQUENCY OF USE, THE WEATHER. FIRST DOSE OF FILTERS

WARNING: DO NOT USE IT WITH OTHER PRODUCTS. IT CAN GENERATE DANGEROUS GAS (CHLORINE)

PHYSICAL AND CHEMICAL PROPERTIES

	HITE TABLETS WITH
BLUE PIGMENTS (200 GRAMS) ODOUR CH	LORINE PUNGENT
	OUND 12 g/l
	OUND 3.5
SOLUBILITY 10	g/l
MELTING POT >	OF 200 °C

CHECKS:

THE DILUTED PRODUCT CAN BE QUANTIFIED AND CHECKED BY MEANS OF DPD REAGENTS.

WARNINGS AND POTENTIAL HAZARDS

CLASSIFICATION Xn: HARMFUL O: COMBUSTIVE AGENT N: ENVIRONMENTALLY HAZARDOUS

- R 8 CONTACT WITH COMBUSTIBLE MATERIAL MAY CAUSE FIRE
- R 22: HARMFUL IF SWALLOWED
- R 31. CONTACT WITH ACIDS LIBERATES TOXIC GAS (CHLORINE)
- R 36/37: IRRITATING TO EYES/RESPIRATORY SYSTEM
- R50/53 : VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT
- S 2: KEEP OUT OF THE REACH OF CHILDREN
- S 8: KEEP CONTAINER DRY
- S 13: KEEP AWAY FROM FOOD, DRINK AND ANIMAL FOODSTUFFS
- S 26: IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE
- S 35: THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF IN A SAFE WAY
- S 41: IN CASE OF FIRE AND/OR EXPLOSION DO NOT BREATHE FUMES
- S 45: IN CASE OF ACCIDENT OR IF YOU FEEL UNWELL SEEK MEDICAL ADVICE IMMEDIATELY (SHOW THE LABEL WHERE POSSIBLE)
- S 60: THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF AS HAZARDOUS WASTE
- S 61: AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEET

COMPOSITION:

TRICHLOROISOCYANURIC ACID; SOLUBLE METAL SALTS

PACKAGING:

5, 10 E 25 KG BARREL – 1 KG CAN

MULTIFUNZIONE 200 GR. STN

26/02/2013

BARCHEMICALS S.r.l. reserve the right to change the formulation of this product at any time without previous notice. The new technical sheet shall automatically cancel and replace the previous one.

Numero telefonico di chiamata urgente: +39 335 6109383 Sede Legale ed Operativa : Via S. Allende, 14 - 41051 Castelnuovo Rangone (MO) - Italy Phone 0039 59 536502 - Fax 0039 59 536742 e-mail : info@barchemicals.it - http://www.barchemicals.it Azienda Certificata UNI EN ISO 9001 - CERT. N° 4247 Azienda Certificata UNI EN ISO 14001 - CERT. N° 6388







