

CONTROL METAL

METAL AND ANTI-SLIME SEQUESTANT FOR SWIMMING POOLS AND CLOSED-CYCLE CIRCUITS

IDENTIFICATION OF THE SUBSTANCE:

CONTROL METAL HAS BEEN FORMULATED IN ORDER TO AVOID THE PROBLEMS ORIGINATING FROM CALCAREOUS HEAVY METAL DEPOSITS SUCH AS COPPER, IRON, MANGANESE ETC...
IT INHIBITS METAL SURFACE CORROSION.

USE AND DOSAGE :

ADD CONTROL METAL TO THE POINT OF MAXIMUM AGITATION OF POOL WATER TO ENHANCE A HOMOGENEOUS DISTRIBUTION OF THE PRODUCT.

INITIAL DOSAGE:

MEDIUM-HARD WATER: 30-60 g/m³

HARD WATER: 60-100 g/m³

MAINTENANCE DOSAGE:

ACCORDING TO THE DAILY CHANGE OF WATER, IT IS RECOMMENDED TO ADMINISTER 5 - 10 g/m³ EVERY 2 - 3 DAYS.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	AMBER-COLOURED LIQUID
ODOR	ODORLESS
SOLUBILITY IN WATER	COMPLETE
pH OF PRODUCT "AS IS"	9-10
pH (1% solution)	9-10
SPECIFIC GRAVITY AT 25°C	1.2-1.3 Kg/l

CHECKS:

WARNINGS AND HAZARDS IDENTIFICATION

P102: KEEP OUT OF REACH OF CHILDREN

EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATOR:

NONE REQUIRED

HAND PROTECTION: GLOVES

EYE PROTECTION: TOTAL SAFETY GOGGLES

CLOTHING: PROTECTIVE CLOTHING

ADDITIONAL MEASURES: EYE WASH BOTTLES

TLV LIMITS: TLV LIMITS NOT ESTABLISHED

NO SPECIAL PROTECTIONS REQUIRED.

CONTROL METAL STN

HANDLING AND STORAGE

HANDLE WEARING RUBBER GLOVES AND SAFETY GOGGLES.

STORE AT ROOM-TEMPERATURE PROTECTED AGAINST DIRECT SUNLIGHT.

FIRST-AID MEASURES

SKIN: WASH WITH COPIOUS AMOUNTS OF FLOWING WATER

EYE: WASH WITH COPIOUS AMOUNTS OF FLOWING WATER IMMEDIATELY, GENTLY PRIZING OPEN EYELIDS TO ENSURE EFFICIENT WASHING.
IF NECESSARY, ASK FOR A SPECIALIST'S EXAMINATION.

INGESTION: WASH OUT MOUTH WITH COPIOUS AMOUNTS OF WATER AND DRINK WATER.
GET MEDICAL ATTENTION AS SOON AS POSSIBLE.

INHALATION: NOT APPLICABLE.

COMPOSITION:

IT CONTAINS SULFONIC TRIMETHYLEN AMINE ACID CONC. <15% AND SPECIFIC CO-FORMULATORS.

PACKAGING

10 LTR. BARREL

TRANSPORT INFORMATION

TRANSPORT BY ROAD: ADR NOT APPLICABLE

BARCHEMICALS S.r.l. reserve the right to change the formulation of this product at any time without previous notice.
The new technical sheet shall automatically cancel and replace the previous one.

Numero telefonico di chiamata urgente: +39 335 6109383

Sede Legale ed Operativa : Via S. Allende, 14 - 41051 Castelnuovo Rangone (MO) - Italy

Phone 0039 59 536502 - Fax 0039 59 536742 e-mail : info@barchemicals.it - <http://www.barchemicals.it>

Azienda Certificata UNI EN ISO 9001 - CERT. N° 4247 Azienda Certificata UNI EN ISO 14001 - CERT. N° 6388