

**POOL Line****TECHNICAL SHEET No. 651****FLOC SUPER****FLOCCULANT BASED ON ALUMINUM AND INORGANIC POLYELECTROLYTES****IDENTIFICATION OF THE SUBSTANCE:**

IT INCREASE THE POWER OF NORMAL QUARTZ FILTERS.  
IT IS ESPECIALLY DESIGNED FOR REMOVE TRACES OF  
IRON FROM WATER THAT ARE VERY RICH OF IT.

**USE AND DOSAGE :**

DILUTE THE PRODUCT TO 10% IN WATER AND ADJUST  
THE PROPER DOSING PUMP RUN.  
IF YOU RUN WITH THE MANUAL DOSAGE PUT DIRECTLY  
IN THE SKIMMER THE PRE-DILUTE PRODUCT.  
PH VALUES SUGGESTED: BETWEEN 7.6 AND 7.8. T  
HE PRESENCE OF PRECIPITATE NOT CHANGE THE  
CHARACTERISTICS OF THE PRODUCT

MEDIUM DOSAGE: 1 – 2 cc/mc OF WATER PER DAY.  
MASSIVE TREATMENT, INDICATIVE DOSAGE: 10 cc/mc OF  
WATER.

1cc=1ml

**PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	LIQUID
ODOR	ODORLESS
SOLUBILITY IN WATER	COMPLETE
pH del PRODOTTO TAL QUALE	-
pH solution 1%	4
SPECIFIC GRAVITY AT 25°C	1,21 Kg/l

**WARNINGS AND POTENTIAL HAZARDS**

THE PRODUCT IS **IRRITANT**

**HAZARD STATEMENTS:**

H290 MAY BE CORROSIVE TO METALS.

H318 CAUSES SERIOUS EYE DAMAGE.

**PRECAUTIONARY STATEMENTS:**

P102 KEEP OUT OF REACH OF CHILDREN.

P234 KEEP ONLY IN ORIGINAL CONTAINER.

P280 WEAR PROTECTIVE GLOVES/CLOTHING AND  
EYE/FACE PROTECTION.

P305+P351+P338 IF IN EYES: RINSE CAUTIOUSLY WITH  
WATER FOR SEVERAL MINUTES. REMOVE CONTACT  
LENSES, IF PRESENT AND EASY TO DO. CONTINUE  
RINSING.

P390 ABSORB SPILLAGE TO PREVENT MATERIAL  
DAMAGE.

P406 STORE IN CORROSIVE RESISTANT CONTAINER.

DON'T USE DIRECTLY THE PRODUCTS IN POOL, DON'T  
USE WITH DIATOMEE FILTER.

**COMPOSITION:**

PRE-DISPERSED ALLUMINIUM AND INORGANIC

POLYELECTROLYTES.

**PACKAGING**

10 LITRES CAN – 5 LITRES CAN – 1 LITRE BOTTLE

**TRANSPORT INFORMATION**

TRANSPORT BY ROAD: UN 2581, ALUMINIUM CHLORIDE  
SOLUTION, 8, III, ADR